



Cisco

300-825

Implementing Cisco Collaboration Conferencing (CLCNF)

Questions & Answers PDF

For More Information:

<https://www.certswarrior.com/>

Features:

- 90 Days Free Updates
- 30 Days Money Back Guarantee
- Instant Download Once Purchased
- 24/7 Online Chat Support
- Its Latest Version

Latest Version: 6.0

Question: 1

Which Expressway-E service or protocol is required for external web app participants to join a Cisco Meeting Server version 3.0 conference as guests?

- A. XMPP
- B. TURN
- C. SIP
- D. H.323

Answer: B

Question: 2

Refer to the exhibit.

<pre>CMS1> ipv4 a IPv4 configuration: address 10.0.101.120 default true dhcp false enabled true gateway 10.0.101.1 prefixlen 24 route 10.0.0.0/8 CMS1> ipv4 b IPv4 configuration: address 192.168.2.20 dhcp false enabled true gateway 192.168.2.1 prefixlen 24 route 192.168.0.0/16</pre>	<pre>Subnets: Headquarters: Network: 10.0.0.0/8 Services: All allowed Management Network: Network: 192.168.2.0/24 Services: Only HTTP, HTTPS, SSH, LDAP Remote Site: Network: 192.168.10.0/24 Services: All allowed</pre>
--	---

An administrator troubleshoots an issue with Cisco Meeting Server. Endpoints that call from the remote site cannot connect, but endpoints that call from headquarters can connect. What should the administrator do to resolve this issue?

- A. Add a route for 192.168.10.0/24 to interface b.
- B. Set interface b as the default interface.
- C. Remove the route for 192.168.0.0/16 from interface b.
- D. Enable DHCP on interface a but not on interface b.

Answer: A

Question: 3

An engineer configures Cisco Meeting Server as a conference resource for Cisco UCM. Cisco UCM has a secure SIP trunk to Cisco Meeting Server, but the server does not register to Cisco UCM. Which configuration resolves this issue?

- A. Ensure that the SIP trunk from Cisco UCM to Cisco Meeting Server is a secure trunk using port 5061.
- B. Add Cisco Meeting Server to the Cisco UCM SIP trunk with an IP address and not an FQDN.
- C. Set the Web Admin port on the Conference Bridge settings to match Cisco Meeting Server.
- D. Configure an MRGL that contains Cisco Meeting Server to be associated with device pools.

Answer: D

Reference: <https://www.cisco.com/c/en/us/support/docs/conferencing/meeting-server/213820-configure-cisco-meeting-server-and-cucm.html>

Question: 4

Refer to the Following:

Content-Type: application/sdp

Content-Length: 4938

v=0

o=Acano 0 0 IN IP4 10.0.101.120

s=-

c=IN IP4 10.0.101.120

b=CT:16

t=0 0

m=audio 50262 RTP/AVP 108 107 109 110 9 99 111 100 104 103 0 8 15 102 18 13 118 101

a=crypto:1 AEAD_AES_128_GCM *****|2^48

a=crypto:2 AEAD_AES_256_GCM
*****|2^48

a=crypto:3 AES_CM_128_HMAC_SHA1_80
*****|2^48

a=crypto:4 AES_CM_128_HMAC_SHA1_32
*****|2^48

<details omitted>

m=video 50264 RTP/AVP 97 116 114 96 34 31 100 121

b=TIAS:16000

a=crypto:1 AEAD_AES_128_GCM *****|2^48

a=crypto:2 AEAD_AES_256_GCM
*****|2^48

a=crypto:3 AES_CM_128_HMAC_sha1_80
*****|2^48

a=crypto:4 AES_CM_128_HMAC_sha1_32
*****|2^48

a=content:main

a=sendrecv

a=sprop-source:1 count=2;policies=cs:1

a=sprop-simul:1 1 *

a=rtcp-fb:* nack pli

a=rtcp-fb:* ccm fir

a=rtcp-fb:* ccm cisco-scr

a=extmap:1 <http://protocols.cisco.com/virtualid>

a=extmap:2 <http://protocols.cisco.com/framemarking>

a=rtpmap:97 H264/90000

a=fmtp:97 profile-level-id=42800a;max-mpbs=489600;max-fs=8160;max-cpb=4000;max-dpd=4752;max-fps=6000

Users report that they do not see a high-quality picture on the high-definition endpoints when they call into Cisco Meeting Server. An engineer must extract the SDP that is offered by Cisco Meeting Server from the SIP traces to troubleshoot. What is the cause of this issue?

- A. Cisco Meeting Server is not configured for H.265 to support high-definition video calling.
- B. The AES ciphers are not compatible with high-definition video calling.
- C. The Content-Length value in the SDP does not support high-definition video calling.
- D. The SIP call bandwidth is not at a value that supports high-definition video calling.

Answer: D

Question: 5

```
<?xml version="1.0"?>
<coSpace id="2cc9110e-a36a-4173-8cb5-660c3d1e7c92">
  <name>CCNP Collaboration</name>
  <autoGenerated>>false</autoGenerated>
  <uri>8001</uri>
  <callId>849274932</callId>
  <passcode>1234</passcode>
  <secret>XnKexB0yWQ2iwfu0Ce6AWQ</secret>
  <numAccessMethods>2</numAccessMethods>
</coSpace>
```

Refer to the exhibit. When a user dials 8001 to connect to a space that is hosted on Cisco Meeting Server, the user is prompted for a pin. The prompt says the user should press # to connect to a meeting without a pin, but guests and hosts must enter a pin before connecting to the meeting.

Which configuration change resolves this issue?

- A. The secret value must be changed to be solely numeric instead of alpha-numeric.
- B. The passcode must be changed to be longer than four digits.
- C. All access methods that are associated with the space must be changed to include a pin.
- D. A callLegProfile must be created and associated with the space so that pins are not optional.

Answer: D

Reference: <https://www.cisco.com/c/en/us/support/docs/conferencing/meeting-server/213552-configure-and-troubleshoot-guest-and-hos.html#anc10>



CERTSWARRIOR

FULL PRODUCT INCLUDES:

Money Back Guarantee



Instant Download after Purchase



90 Days Free Updates



PDF Format Digital Download



24/7 Live Chat Support



Latest Syllabus Updates



For More Information – Visit link below:

<http://www.certswarrior.com>

Discount Coupon Code:

CERTSWARRIOR10

We Accept

PayPal