



Dell EMC

DES-4122

Specialist - Implementation Engineer PowerEdge Version 2.0

Questions & Answers PDF

For More Information:

<https://www.certswarrior.com/>

Features:

- 90 Days Free Updates
- 30 Days Money Back Guarantee
- Instant Download Once Purchased
- 24/7 Online Chat Support
- Its Latest Version

Latest Version: 7.0

Question: 1

What is a requirement to operate GPUs in a Dell EMC PowerEdge R740 server?

- A. All GPU cards must be installed at the same time
- B. All GPU cards must be of the same type but can be a different model
- C. All GPU cards must be of the same type and model
- D. All GPU cards must be installed on the same riser card.

Answer: C

Question: 2

What is used by the Lifecycle Controller to directly back up the server profile on a 14G Dell EMC PowerEdge server?

- A. Network share
- B. vFlash SD card
- C. USB Flash drive
- D. IDSDM SD card

Answer: A

Question: 3

Where is the data stored to allow Easy Restore to successfully complete a system board replacement?

- A. NAND Flash module on the disk drive mid plane
- B. IDSDM SD card
- C. vFlash SD card
- D. Serial Flash storage in the server's front panel

Answer: C

Question: 4

When does a customer require the Service Tag of the Dell EMC PowerEdge server?

- A. First time logging in to iDRAC
- B. First time accessing the BIOS
- C. Activating the OS
- D. Obtaining warranty information

Answer: B

Question: 5

DRAG DROP

What is the correct order of steps taken during the BIOS/UEFI Recovery process?

System boots to primary ROM	Step 1
iDRAC extracts the recovery BIOS image from a DUP saved in the control panel from the factory	Step 2
System disables the recovery ROM	Step 3
Connect to CLI of the affected server's iDRAC and run the racadm recover BIOS Setup 1-1 command	Step 4
System initiates the recovery ROM and launches a BIOS update job	Step 5

Answer:

System boots to primary ROM	System boots to primary ROM
iDRAC extracts the recovery BIOS image from a DUP saved in the control panel from the factory	iDRAC extracts the recovery BIOS image from a DUP saved in the control panel from the factory
System disables the recovery ROM	Connect to CLI of the affected server's iDRAC and run the racadm recover BIOS Setup 1-1 command
Connect to CLI of the affected server's iDRAC and run the racadm recover BIOS Setup 1-1 command	System disables the recovery ROM
System initiates the recovery ROM and launches a BIOS update job	System initiates the recovery ROM and launches a BIOS update job



CERTSWARRIOR

FULL PRODUCT INCLUDES:

Money Back Guarantee



Instant Download after Purchase



90 Days Free Updates



PDF Format Digital Download



24/7 Live Chat Support



Latest Syllabus Updates



For More Information – Visit link below:

<http://www.certswarrior.com>

Discount Coupon Code:

CERTSWARRIOR10

We Accept

PayPal