

# Juniper JN0-231

## Juniper Security, Associate Exam

**Questions&AnswersPDF** 

### ForMoreInformation:

https://www.certswarrior.com/

# **Features:**

- ➤ 90DaysFreeUpdates
- ➤ 30DaysMoneyBackGuarantee
- > InstantDownloadOncePurchased
- ➤ 24/7OnlineChat Support
- ➤ ItsLatestVersion

#### **Latest Version: 8.1**

#### Question: 1

Which two criteria should a zone-based security policy include? (Choose two.)

A. a source port

B. a destination port

C. zone context

D. an action

**Answer: AB** 

#### Explanation:

A security policy is a set of statements that controls traffic from a specified source to a specified destination using a specified service. A policy permits, denies, or tunnels specified types of traffic unidirectionally between two points.

Each policy consists of:

A unique name for the policy.

A from-zone and a to-zone, for example: user@host# set security policies from-zone untrust to-zone untrust

A set of match criteria defining the conditions that must be satisfied to apply the policy rule. The match criteria are based on a source IP address, destination IP address, and applications. The user identity firewall provides greater granularity by including an additional tuple, source-identity, as part of the policy statement.

A set of actions to be performed in case of a match—permit, deny, or reject.

Accounting and auditing elements—counting, logging, or structured system logging.

https://www.juniper.net/documentation/us/en/software/junos/security-policies/topics/topicmap/security-policy-configuration.html

#### Question: 2

You are assigned a project to configure SRX Series devices to allow connections to your webservers. The webservers have a private IP address, and the packets must use NAT to be accessible from the Internet. You do not want the webservers to initiate connections with external update servers on the Internet using the same IP address as customers use to access them.

Which two NAT types must be used to complete this project? (Choose two.)

A. static NAT

B. hairpin NAT

C. destination NAT

D. source NAT

Answer: C, D

#### Question: 3

You are asked to verify that a license for AppSecure is installed on an SRX Series device. In this scenario, which command will provide you with the required information?

A. user@srx> show system license

B. user@srx> show services accounting

C. user@srx> show configuration system

D. user@srx> show chassis firmware

**Answer: A** 

#### Question: 4

Click the Exhibit button.

[edit security policies]
user@vSRX-1# edit from-zone trust to-zone dmz policy Trust-DMZ-Access
[edit security policies from-zone trust to-zone dmz policy Trust-DMZ-Access]
user@vSRX-1# exit

Referring to the exhibit, a user is placed in which hierarchy when the exit command is run?

A.

[edit security policies from-zone trust to-zone dmz] user@vSRX-1#

В.

[edit]

user@vSRX-1#

C.

[edit security policies]

user@vSRX-1#

D.

user@vSRX-1>

**Answer: A** 

#### **Question: 5**

You want to enable the minimum Juniper ATP services on a branch SRX Series device. In this scenario, what are two requirements to accomplish this task? (Choose two.)

- A. Install a basic Juniper ATP license on the branch device.
- B. Configure the juniper-atp user account on the branch device.
- C. Register for a Juniper ATP account on https://sky.junipersecurity.net.
- D. Execute the Juniper ATP script on the branch device.

#### Explanation:

https://manuals.plus/m/95fded847e67e8f456453182a54526ba3224a61a337c47177244d345d1f3b19e.pdf



## FULL PRODUCT INCLUDES:

Money Back Guarantee



Instant Download after Purchase



90 Days Free Updates



PDF Format Digital Download



24/7 Live Chat Support



Latest Syllabus Updates



For More Information – Visit link below:

https://www.certswarrior.com

16 USD Discount Coupon Code: U89DY2AQ